



Standard Of Series CC



External Thread Type CC

Design Features

- Spray Angle : 0°(Liquid column flow)-110°
- Spray Pattern : Flat spray pattern distributes the liquid as a flat - or sheet-type spray.
- Drops : Small- to medium-size,uniform distribution over a wide range of flow rates and pressure.
- Material : BRASS/SS/PP/PVC/PTFE
- Features :Large,unobstructed flow passages minimize clogging.
High impact solid stream provides highest impact per unit area.
Specially tapered spray pattern is ideal for use in manifold.

Applications

- Fire prevention
- Spray cooling
- Air purification
- Cooling and hardening
- Dust control
- Metal treating
- Gas cooling & scrubbing

Performance State

At the stated pressure in bar.

Jet Angle (3 bar)	Capacity Size	Nozzle Type/Inlet Conn.(in.)												Orifice (mm)	Flow Rate Capacity (L/min)												Spray Angle (°)			
		H-VV		H-VVL		H-U					U		0.3bar		1bar	2bar	3bar	4bar	5bar	6bar	7bar	10bar	20bar	35bar	1.5bar	3bar	6bar	14bar		
		1/8	1/4	1/8	1/4	1/8	1/4	3/8	1/2	3/4	1	1-1/4																	2	
50°	5001	●	●	●	●								0.66		0.23	0.32	0.39	0.46	0.51	0.56	0.60	0.72	1.0	1.3	37°	50°	59°	65°		
	5002	●	●	●	●								0.91		0.46	0.64	0.79	0.91	1.0	1.1	1.2	1.4	2.0	2.7	39°	50°	57°	63°		
	5003	●	●	●	●								1.1	0.37	0.68	0.97	1.2	1.4	1.5	1.7	1.8	2.2	3.1	4.0	40°	50°	56°	62°		
	5004	●	●	●	●								1.3	0.50	0.91	1.3	1.6	1.8	2.0	2.2	2.4	2.9	4.1	5.4	42°	50°	56°	61°		
	5005	●	●	●	●								1.4	0.62	1.1	1.6	2.0	2.3	2.5	2.8	3.0	3.6	5.1	6.7	44°	50°	56°	61°		
	5006	●	●	●	●								1.6	0.75	1.4	1.9	2.4	2.7	3.1	3.3	3.6	4.3	6.1	8.1	45°	50°	56°	60°		
	5008	●	●	●	●								1.8	1.0	1.8	2.6	3.2	3.6	4.1	4.5	4.8	5.8	8.2	10.8	45°	50°	55°	60°		
	5010					●	●	●					2.0	1.2	2.3	3.2	3.9	4.6	5.1	5.6	6.0	7.2	10.2	13.5	45°	50°	55°	59°		
	5015									●			2.4	1.9	3.4	4.8	5.9	6.8	7.6	8.4	9.0	10.8	15.3	20	45°	50°	55°	59°		
	5020					●	●	●	●				2.8	2.5	4.6	6.5	7.9	9.1	10.2	11.2	12.1	14.4	20	27	45°	50°	55°	59°		
	5030					●	●	●	●	●			3.6	3.7	6.8	9.7	11.8	13.7	15.3	16.7	18.1	22	31	40	45°	50°	55°	59°		
	5040					●	●	●	●				4.0	5.0	9.1	12.9	15.8	18.2	20	22	24	29	41	54	46°	50°	54°	59°		
	5050					●	●	●	●				4.4	6.2	11.4	16.1	19.7	23	25	28	30	36	51	68	46°	50°	54°	59°		
	5060						●	●	●				4.8	7.5	13.7	19.3	24	27	31	33	36	43	61	81	46°	50°	54°	59°		
	5070						●	●	●	●			5.2	8.7	16.0	23	28	32	36	39	42	50	71	94	46°	50°	54°	59°		
	50100							●	●				6.4	12.5	23	32	39	46	51	56	60	72	102	135	44°	50°	52°	54°		
	50120							●	●				6.7	15.0	27	39	47	55	61	67	72	86	122	162	44°	50°	53°	55°		
	50150							●	●				7.5	18.7	34	48	59	68	76	84	90	108	153	205	45°	50°	52°	55°		
	50200								●				8.7	25	46	64	79	91	102	112	121	144	205	270	46°	50°	52°	55°		
	50400									●			12.7	50	91	129	158	182	205	225	240	290	410	540	46°	50°	52°	55°		
	50500										●	●	13.1	62	114	161	197	230	255	280	300	360	510	680	49°	50°	51°	54°		
	50580										●		13.9	72	132	187	230	265	295	325	350	420	600	780	49°	50°	51°	53°		
	50750											●	15.9	94	171	240	295	340	385	420	455	540	770	1010	49°	50°	51°	53°		
	501000											●	18.3	125	230	325	395	455	510	560	610	720	1020	1350	49°	50°	51°	53°		
	501500											●	22.6	187	340	485	600	690	770	840	910	1080	1530	2020	49°	50°	51°	52°		
	502000											●	26.2	250	460	650	790	910	1020	1120	1210	1440	2040	2700	49°	50°	51°	52°		
40°	4001	●	●	●	●								0.66			0.32	0.39	0.46	0.51	0.56	0.60	0.72	1.0	1.3	26°	40°	52°	59°		
	40015	●	●	●	●								0.79			0.48	0.59	0.68	0.76	0.84	0.90	1.1	1.5	2.0	27°	40°	52°	59°		
	4002	●	●	●	●								0.91		0.46	0.64	0.79	0.91	1.0	1.1	1.2	1.4	2.0	2.7	29°	40°	51°	58°		
	4003	●	●	●	●								1.1		0.68	0.97	1.2	1.4	1.5	1.7	1.8	2.2	3.1	4.0	30°	40°	50°	57°		
	4004	●	●	●	●								1.3		0.91	1.3	1.6	1.8	2.0	2.2	2.4	2.9	4.1	5.4	30°	40°	50°	56°		
	4005	●	●	●	●								1.4		1.1	1.6	2.0	2.3	2.5	2.8	3.0	3.6	5.1	6.7	31°	40°	49°	55°		
	4006	●	●	●	●								1.6		1.4	1.9	2.4	2.7	3.1	3.3	3.6	4.3	6.1	8.1	31°	40°	49°	55°		
	4008	●	●	●	●								1.8	1.0	1.8	2.6	3.2	3.6	4.1	4.5	4.8	5.8	8.2	10.8	31°	40°	47°	53°		
	4010					●	●	●					2.0	1.2	2.3	3.2	3.9	4.6	5.1	5.6	6.0	7.2	10.2	13.5	32°	40°	45°	48°		
	4015					●	●	●					2.4	1.9	3.4	4.8	5.9	6.8	7.6	8.4	9.0	10.8	15.3	20	32°	40°	45°	48°		
	4020					●	●	●	●	●			2.8	2.5	4.6	6.5	7.9	9.1	10.2	11.2	12.1	14.4	20	27	32°	40°	45°	48°		
	4030					●	●	●	●				3.6	3.7	6.8	9.7	11.8	13.7	15.3	16.7	18.1	22	31	40	33°	40°	45°	48°		
	4040					●	●	●	●				4.0	5.0	9.1	12.9	15.8	18.2	20	22	24	29	41	54	34°	40°	45°	48°		
	5050						●	●	●	●			4.4	6.2	11.4	16.1	19.7	23	25	28	30	36	51	68	35°	40°	45°	48°		
	4060						●	●	●	●			4.8	7.5	13.7	19.3	24	27	31	33	36	43	61	81	35°	40°	45°	48°		
	4070						●	●	●	●			5.2	8.7	16.0	23	28	32	36	39	42	50	71	94	35°	40°	45°	48°		
	40100							●	●				6.4	12.5	23	32	39	46	51	56	60	72	102	135	34°	40°	43°	46°		
	40150							●	●				7.5	18.7	34	48	59	68	76	84	90	108	153	205	35°	40°	43°	44°		
	40200							●	●				8.7	25	46	64	79	91	102	112	121	144	205	270	36°	40°	42°	44°		



Jet Angle (3 bar)	Capacity Size	Nozzle Type/Inlet Conn.(in.)												Orifice (mm)	Flow Rate Capacity (L/min)														Spray Angle (°)			
		H-W		H-VVL		H-U				U		0.3 bar	1 bar		2 bar	3 bar	4 bar	5 bar	6 bar	7 bar	10 bar	20 bar	35 bar	1.5 bar	3 bar	6 bar	14 bar					
		1/8	1/4	1/8	1/4	1/8	1/4	3/8	1/2	3/4	1																	1-1/4	2			
25°	2501	●	●	●	●									0.66			0.32	0.39	0.46	0.51	0.56	0.60	0.72	1.0	1.3	14°	25°	34°	42°			
	2502	●	●	●	●									0.91		0.46	0.64	0.79	0.91	1.0	1.1	1.2	1.4	2.0	2.7	15°	25°	33°	40°			
	2503	●	●	●	●									1.1		0.68	0.97	1.2	1.4	1.5	1.7	1.8	2.2	3.1	4.0	15°	25°	33°	40°			
	2504	●	●	●	●									1.3		0.91	1.3	1.6	1.8	2.0	2.2	2.4	2.9	4.1	5.4	16°	25°	32°	39°			
	2505	●	●	●	●									1.4		1.1	1.6	2.0	2.3	2.5	2.8	3.0	3.6	5.1	6.7	16°	25°	32°	39°			
	2506	●	●	●	●									1.6		1.4	1.9	2.4	2.7	3.1	3.3	3.6	4.3	6.1	8.1	17°	25°	31°	38°			
	2508	●	●	●	●									1.8		1.8	2.6	3.2	3.6	4.1	4.5	4.8	5.8	8.2	10.8	17°	25°	31°	38°			
	2510					●	●							2.0		2.3	3.2	3.9	4.6	5.1	5.6	6.0	7.2	10.2	13.5	18°	25°	31°	37°			
	2515					●	●	●						2.4		3.4	4.8	5.9	6.8	7.6	8.4	9.0	10.8	15.3	20	18°	25°	31°	37°			
	2520					●	●	●	●					2.8	2.5	4.6	6.5	7.9	9.1	10.2	11.2	12.1	14.4	20	27	19°	25°	31°	37°			
	2530					●	●	●	●					3.6	3.7	6.8	9.7	11.8	13.7	15.3	16.7	18.1	22	31	40	20°	25°	30°	36°			
	2540						●	●	●					4.0	5.0	9.1	12.9	15.8	18.2	20	22	24	29	41	54	21°	25°	29°	35°			
	2550						●	●	●					4.4	6.2	11.4	16.1	19.7	23	25	28	30	36	51	68	21°	25°	29°	35°			
	2560						●	●	●					4.8	7.5	13.7	19.3	24	27	31	33	36	43	61	81	22°	25°	29°	35°			
	2570						●	●	●					5.2	8.7	16.0	23	28	32	36	39	42	50	71	94	22°	25°	29°	35°			
	25100							●	●	●				6.4	12.5	23	32	39	46	51	56	60	72	102	135	23°	25°	28°	32°			
	25150							●	●	●				7.5	18.7	34	48	59	68	76	84	90	108	153	205	24°	25°	28°	30°			
25200								●					8.7	25	46	64	79	91	102	112	121	144	205	270	24°	25°	26°	29°				
25500									●	●			13.1	62	114	161	197	230	255	280	300	360	510	680	24°	25°	26°	29°				
25750										●	●		15.9	94	171	240	295	340	385	420	455	540	770	1010	24°	25°	26°	28°				
251000											●		18.7	125	230	325	395	455	510	560	610	720	1020	1350	24°	25°	26°	28°				
15°	1501	●	●	●	●									0.66			0.32	0.39	0.46	0.51	0.56	0.60	0.72	1.0	1.3	15°	24°	28°				
	1502	●	●	●	●									0.91			0.64	0.79	0.91	1.0	1.1	1.2	1.4	2.0	2.7	6°	15°	22°	27°			
	1503	●	●	●	●									1.1			0.97	1.2	1.4	1.5	1.7	1.8	2.2	3.1	4.0	6°	15°	22°	27°			
	1504	●	●	●	●									1.3			1.3	1.6	1.8	2.0	2.2	2.4	2.9	4.1	5.4	7°	15°	21°	26°			
	1505	●	●	●	●									1.4			1.6	2.0	2.3	2.5	2.8	3.0	3.6	5.1	6.7	7°	15°	21°	26°			
	1506	●	●	●	●									1.6		1.4	1.9	2.4	2.7	3.1	3.3	3.6	4.3	6.1	8.1	8°	15°	21°	26°			
	1508	●	●	●	●									1.8		1.8	2.6	3.2	3.6	4.1	4.5	4.8	5.8	8.2	10.8	9°	15°	20°	25°			
	1510					●	●							2.0		2.3	3.2	3.9	4.6	5.1	5.6	6.0	7.2	10.2	13.5	10°	15°	19°	24°			
	1515					●	●	●						2.4		3.4	4.8	5.9	6.8	7.6	8.4	9.0	10.8	15.3	20	10°	15°	19°	24°			
	1520					●	●	●						2.8		4.6	6.5	7.9	9.1	10.2	11.2	12.1	14.4	20	27	10°	15°	19°	23°			
	1530					●	●	●						3.6		6.8	9.7	11.8	13.7	15.3	16.7	18.1	22	31	40	10°	15°	19°	21°			
	1540					●	●	●						4.0		9.1	12.9	15.8	18.2	20	22	24	29	41	54	10°	15°	18°	21°			
	1550						●	●	●	●				4.4		11.4	16.1	19.7	23	25	28	30	36	51	68	11°	15°	18°	21°			
0°	0003					●	●							1.0	0.37	0.68	0.97	1.2	1.4	1.5	1.7	1.8	2.2	3.1	4.0							
	0004					●	●							1.2	0.50	0.91	1.3	1.6	1.8	2.0	2.2	2.4	2.9	4.1	5.4							
	0005					●	●							1.3	0.62	1.1	1.6	2.0	2.3	2.5	2.8	3.0	3.6	5.1	6.7							
	0006					●	●							1.5	0.75	1.4	1.9	2.4	2.7	3.1	3.3	3.6	4.3	6.1	8.1							
	0008					●	●							1.7	1.0	1.8	2.6	3.2	3.6	4.1	4.5	4.8	5.8	8.2	10.8							
	0010					●	●							1.9	1.2	2.3	3.2	3.9	4.6	5.1	5.6	6.0	7.2	10.2	13.5							
	0015					●	●							2.3	1.9	3.4	4.8	5.9	6.8	7.6	8.4	9.0	10.8	15.3	20							
	0020					●	●	●						2.7	2.5	4.6	6.5	7.9	9.1	10.2	11.2	12.1	14.4	20	27							
	0030					●	●							3.6	3.7	6.8	9.7	11.8	13.7	15.3	16.7	18.1	22	31	40							
	0040					●	●							4.0	5.0	9.1	12.9	15.8	18.2	20	22	24	29	41	54							
	0050						●							4.4	6.2	11.4	16.1	19.7	23	25	28	30	36	51	68							
	0060						●							4.8	7.5	13.7	19.3	24	27	31	33	36	43	61	81							
	0070						●	●						5.2	8.7	16.0	23	28	32	36	39	42	50	71	94							
	0080						●	●						5.2	10.0	18.2	26	32	36	41	45	48	58	82	108							
	00100							●						6.0	12.5	23	32	39	46	51	56	60	72	102	135							
	00120							●						6.4	15.0	27	39	47	55	61	67	72	86	122	162							
	00150								●					7.5	18.7	34	48	59	68	76	84	90	108	153	205							
	00200								●					8.3	25	46	64	79	91	102	112	121	144	205	270							
	00250								●					9.5	31	57	81	99	114	127	140	151	180	255	340							
	00350									●				11.1	44	80	113	138	160	178	195	210	255	360	475							
	00700													15.5	87	160	225	275	320	355	390	420	510	720	950							
	001000										●			19.1	125	230	325	395	460	510	560	610	720	1020	1350							
	001100											●		19.8	140	255	355	435	500	560	620	670	790	1120	1490							
001400												●	22.2	175	320	455	560	640	720	780	850	1010	1430	1890								
001800												●	25.4	225	410	580	710	820	920	1010	1090	1300	1840	2430								
002000												●	26.6	250	460	650	790	910	1020	1120	1210	1440	2040	2700								
003500												●	34.9	440	800	1130	1380	1600	1790	1960	2110	2520	3570	4720								



Performance State

• Standard Angle

At the stated pressure in bar.

Spray Angle	Capacity Size	Orifice (mm)	Flow Rate Capacity (L/min)											Spray Angle (°)		
			0.5bar	1bar	1.5bar	2bar	3bar	4bar	5bar	6bar	7bar	10bar	35bar	0.5bar	1.5bar	6bar
65°	650033	0.28	-	-	0.09	0.11	0.13	0.15	0.17	0.18	0.2	0.24	0.45	-	47	76
	650050	0.46	-	-	0.14	0.16	0.2	0.23	0.26	0.28	0.3	0.36	0.67	-	48	75
	650067	0.53	-	-	0.19	0.22	0.26	0.31	0.33	0.37	0.4	0.47	0.9	-	50	75
	6501	0.66	-	0.23	0.28	0.32	0.39	0.46	0.51	0.56	0.60	0.72	1.3	51	65	74
	65015	0.79	-	0.34	0.42	0.48	0.59	0.68	0.76	0.84	0.90	1.1	2.0	51	65	74
	6502	0.91	0.32	0.46	0.56	0.64	0.79	0.91	1.0	1.1	1.2	1.4	2.7	52	65	73
	65025	1.0	0.40	0.57	0.70	0.81	0.99	1.1	1.3	1.4	1.5	1.8	3.4	52	65	73
	6503	1.1	0.48	0.68	0.83	0.97	1.2	1.4	1.5	1.7	1.8	2.2	4.0	53	65	72
	6504	1.3	0.65	0.91	1.1	1.3	1.6	1.8	2.0	2.2	2.4	2.9	5.4	53	65	72
	6505	1.4	0.80	1.1	1.3	1.6	2.0	2.3	2.5	2.8	3.0	3.6	6.7	53	65	72
	6506	1.6	0.97	1.4	1.7	1.9	2.4	2.7	3.1	3.3	3.6	4.3	8.1	54	65	72
	6508	1.8	1.3	1.8	2.2	2.6	3.2	3.6	4.1	4.5	4.8	5.8	10.8	55	65	71
	6510	2.0	1.5	2.3	2.8	3.2	3.9	4.6	5.1	5.6	6.0	7.2	13.5	56	65	71
	6515	2.4	2.5	3.4	4.2	4.8	5.9	6.6	7.6	8.4	9.0	10.8	20	56	65	70
	6520	2.8	3.2	4.6	5.6	6.5	7.9	9.1	10.2	11.2	12.1	14.4	27	57	65	70
	6530	3.6	4.8	6.8	8.3	9.7	11.8	13.7	15.3	16.7	18.1	22	40	58	65	69
	6540	4.0	6.5	9.1	11.1	12.9	15.8	18.2	20	22	24	29	54	59	65	68
	6550	4.4	8.0	11.4	14.0	16.1	19.7	23	25	28	30	36	68	60	65	68
	6560	4.8	9.7	13.7	16.8	19.3	24	27	31	33	36	43	81	60	65	68
	6570	5.2	11.2	16.0	19.6	23	28	32	36	39	42	50	94	60	65	68
	65100	6.4	16.1	23	28.2	32	39	46	51	56	60	72	135	58	65	69



• Wide Angle

At the stated pressure in bar.

Spray Angle	Capacity Size	Orifice (mm)	Flow Rate Capacity (L/min)											Spray Angle (°)		
			0.5bar	1bar	1.5bar	2bar	3bar	4bar	5bar	6bar	7bar	10bar	35bar	0.5bar	1.5bar	6bar
110°	11001	0.66	0.15	0.23	0.28	0.32	0.39	0.46	0.51	0.56	0.60	0.72	1.3	94	110	121
	110015	0.79	0.25	0.34	0.42	0.48	0.59	0.68	0.76	0.84	0.90	1.1	2.0	97	110	121
	11002	0.91	0.32	0.46	0.56	0.64	0.79	0.91	1.0	1.1	1.2	1.4	2.7	98	110	120
	11003	1.1	0.48	0.68	0.83	0.97	1.2	1.4	1.5	1.7	1.8	2.2	4.0	99	110	120
	11004	1.3	0.65	0.91	1.1	1.3	1.6	1.8	2.0	2.2	2.4	2.9	5.4	100	110	119
	11005	1.4	0.80	1.1	1.3	1.6	2.0	2.3	2.5	2.8	3.0	3.6	6.7	100	110	118
	11006	1.6	0.97	1.4	1.7	1.9	2.4	2.7	3.1	3.3	3.6	4.3	8.1	101	110	117
	11008	1.8	1.3	1.8	2.2	2.6	3.2	3.6	4.1	4.5	4.8	5.8	10.8	102	110	117
	11010	2.0	1.5	2.3	2.8	3.2	3.9	4.6	5.1	5.6	6.0	7.2	13.5	103	110	117
	11015	2.4	2.5	3.4	4.2	4.8	5.9	6.8	7.6	8.4	9.0	10.8	20	104	110	117
95°	11020	2.8	3.2	4.6	5.6	6.5	7.9	9.1	10.2	11.2	12.1	14.4	27	105	110	117
	9501	0.66	0.15	0.23	0.28	0.32	0.39	0.46	0.51	0.56	0.60	0.72	1.3	81	95	105
	95015	0.79	0.25	0.34	0.42	0.48	0.59	0.68	0.76	0.84	0.90	1.1	2.0	82	95	105
	9502	0.91	0.32	0.46	0.56	0.64	0.79	0.91	1.0	1.1	1.2	1.4	2.7	82	95	105
	9503	1.1	0.48	0.68	0.83	0.97	1.2	1.1	1.5	1.7	1.8	2.2	4.0	83	95	104
	9504	1.3	0.65	0.91	1.1	1.3	1.6	1.8	2.0	2.2	2.4	2.9	5.4	84	95	103
	9505	1.4	0.80	1.1	1.3	1.6	2.0	2.3	2.5	2.8	3.0	3.6	6.7	84	95	102
	9506	1.6	0.97	1.4	1.7	1.9	2.4	2.7	3.1	3.3	3.6	4.3	8.1	86	95	101
	9508	1.8	1.3	1.8	2.2	2.6	3.2	3.6	4.1	4.5	4.8	5.8	10.8	87	95	100
	9510	2.0	1.5	2.3	2.8	3.2	3.9	4.6	5.1	4.6	6.0	7.2	13.5	89	95	100
	9515	2.4	2.5	3.4	4.2	4.8	5.9	6.8	7.6	8.4	9.0	10.8	20	90	95	100
	9520	2.8	3.2	4.6	5.6	6.5	7.9	9.1	10.2	11.2	12.1	14.4	27	90	95	100
	9530	3.6	4.8	6.8	8.3	9.7	11.8	13.7	15.3	16.7	18.1	22	40	91	95	101
	9540	4.0	6.5	9.1	11.1	12.9	15.8	18.2	20	22	24	29	54	92	95	100
	9550	4.4	8.0	11.4	14.0	16.1	19.7	23	25	28	30	36	68	93	95	99
80°	9560	4.8	9.7	13.7	16.8	19.3	24	27	31	33	36	43	81	93	95	99
	9570	5.2	11.2	16.0	19.6	23	28	32	36	39	42	50	94	93	95	99
	95100	6.4	16.1	23	28.2	32	39	46	51	56	60	72	135	93	95	99
	8001	0.66	-	0.23	0.28	0.32	0.39	0.46	0.51	0.56	0.60	0.72	1.3	68	80	89
	80015	0.79	-	0.34	0.42	0.48	0.59	0.68	0.76	0.84	0.90	1.1	2.0	68	80	89
	8002	0.91	0.32	0.46	0.56	0.64	0.79	0.91	1.0	1.1	1.2	1.4	2.7	69	80	88
	8003	1.1	0.48	0.68	0.83	0.97	1.2	1.1	1.5	1.7	1.8	2.2	4.0	70	80	87
	8004	1.3	0.65	0.91	1.1	1.3	1.6	1.8	2.0	2.2	2.4	2.9	5.4	71	80	86
	8005	1.4	0.80	1.1	1.3	1.6	2.0	2.3	2.5	2.8	3.0	3.6	6.7	71	80	86
	8006	1.6	0.97	1.4	1.7	1.9	2.4	2.7	3.1	3.3	3.6	4.3	8.1	72	80	85
	8008	1.8	1.3	1.8	2.2	2.6	3.2	3.6	4.1	4.5	4.8	5.8	10.8	72	80	84
	8010	2.0	1.5	2.3	2.8	3.2	3.9	4.6	5.1	4.6	6.0	7.2	13.5	73	80	84
	8015	2.4	2.5	3.4	4.2	4.8	5.9	6.8	7.6	8.4	9.0	10.8	20	74	80	83
	8020	2.8	3.2	4.6	5.6	6.5	7.9	9.1	10.2	11.2	12.1	14.4	27	74	80	83
	8030	3.6	4.8	6.8	8.3	9.7	11.8	13.7	15.3	16.7	18.1	22	40	74	80	83
	8040	4.0	6.5	9.1	11.1	12.9	15.8	18.2	20	22	24	29	54	74	80	83
	8050	4.4	8.0	11.4	14.0	16.1	19.7	23	25	28	30	36	68	74	80	83
	8060	4.8	9.7	13.7	16.8	19.3	24	27	31	33	36	43	81	75	80	83
	8070	5.2	11.2	16.0	19.6	23	28	32	36	39	42	50	94	75	80	83
	80100	6.4	16.1	23	28.2	32	39	46	51	56	60	72	135	75	80	83

For NPT threaded connections, add the letter "N" before the nozzle connection size.

Order Info

CC - 1/4 - SS - 6505
| | | |
Nozzle Type Inlet Conn Material Code Orifice

For NPT threaded connections, add the letter "N" before the nozzle connection size.